



**Put the power of Dingo on your team**

## ▶ Model K9-3 Specifications

### FACTS AT A GLANCE

#### Dingo K9-3

##### Performance

Hydraulics:	2 pumps
Pump Sizes:	Petrol = 9 & 3cc Pro Series = 11 & 3cc
Hydraulic Pressure:	206 Bar (3000psi)
Hydraulic Pump Output:	43 l/min
Max Travel Speed:	7.4 Km/hr
Rate Lift Capacity:	SWL: 250kg MWL: 500kg
Wheel Motors:	2x29 cu in

##### Engine - Kohler Petrol

Power:	16.9 kW (23hp)
--------	----------------

##### Engine - Perkins Diesel

Power:	15 kW (20hp)
--------	--------------

##### Dimensional Specifications

A. Overall Width:	1050mm
B. Overall Length:	1565mm
C. Overall Height:	1200mm
D. Maximum Operating Height with 4 in 1 Bucket:	2080mm
E. Turning Radius with 4 in 1 Bkt:	1300mm
F. Angle of Departure:	20°
G. Wheel Base:	710-800mm
H. Ground Clearance:	135mm
I. Dump Height with Std Bkt:	1240mm
J. Reach Fully Raised Std Bkt:	600mm
K. Dump Height with 4 in 1 Bkt:	1750mm
L. Reach Fully Raised 4 in 1:	600mm
M. Height to Hinge Pin:	1680mm
N. Machine width with 4 in 1 Bkt:	1050mm
Tyre Size:	18 x 8.5 x 8 (6 Ply) std
Hydraulic Reserve Capacity:	60L
Filtration:	10 Micron
Machine Mass:	Kohler = 653kg Perkins = 742kg
Security Immobiliser:	Optional

##### Warranty

Engine Warranty	3 years
Product Warranty	3 years / 1,000 hours

