

SMART PEOPLE HIRE FROM...

SMART HIRE



P33FS

Frequency	50Hz	Voltage	240/415	
Power ESP	33 kVA	26 kW	Rated Speed RPM	1500
Power PRP	30 kVA	24 kW	Power Factor	0.8
Prime	AMPS	Fuel Capacity	170 Litre	
Amps				

Standby: This rating is for the supply of continuous electrical power, at variable load, in the event of a utility power failure. No overload is permitted to standard reference conditions ISO 8528

Prime: This rating is for the supply of continuous electrical power, at variable load, in lieu of commercially purchase power. There is no limitation on the annual hours of operation and 10% over load power can be supplied for 1 hour in 12.

SGEnergy has the right to modify any feature without prior notice. Weights and dimensions based on standard products.

Illustrations may include optional equipment. Technical data described in this catalogue correspond to the available information at the moment of printing. The illustrations and images are indicative and may not coincide in their entirety with the product



Standard Features

- Galvanised Steel Acoustic Canopy
- Rental Skid Base
- Integrated Fork Pockets
- High Quality Powder Coat Finish
- Manual Sump Oil Drain Pump
- Door Open Stays
- Lockable Maintenance Access Doors
- Mechanical & Hot Component Guards
- Fully Bunded Base Frame
- Control Panel Viewing Window
- Sound Proofing - Rockwool
- Long Run Integrated Diesel Tank
- 50 Degree Cooling Package
- Anti Vibration Mounts
- Anti Condensation Heaters

Engine Specifications

Manufacturer	FPT / IVECO	Fuel Consumption 100% PRP	7.7 l/ph
Model	S8000AM1.S500	Fuel Consumption 75 % PRP	6.0l/ph
Engine Type	Four cycle, 3 Cylinder Diesel	Fuel Consumption 50 % PRP	4.3 l/ph
Injection Type	direct injection	Displacement	2.9 L
Aspiration Type	Natural Aspiration	Compression Ratio	17:1
Bore and Stroke	104 mm x 115 mm		

Alternator Specifications

Manufacturer	Mecce Alte	Poles	4
Model	ECP28 VL4C 3	Insulation	H Class
Prime Amps perφ	Amps	Voltage Regulator	DSR

Dimensions

Length	2300 mm	Width	900 mm
Height	1650 mm	Weight (Excl Fuel)	1150 kg Excl Fuel

Controller

DSE 7320 MKII Controller (Standard)

Outlets

2 x 15A Single Phase & 1 x 32A 3Phase